

APPLICATIONS

The HT45 harness is simple to use and easy to adjust. It is designed for all operations where the operator needs to use the fall arrest from the front (roofer, ladder work).

The sternal attachment point facilitates the handling of rope grabbers and ensures better comfort at the workstation. Its ergonomic design ensures optimum comfort. It is designed for long duration work.

This technical harness is widely used for work on roofs, ladders and scaffolding.

This harness is ideal for construction work.



TECHNICAL CHARACTERISTICS

- 1 back attachment point, 1 sternal attachment point.
- Quick adjustment of shoulder straps by sliding bar buckle.
- Fastening and adjustment of straps by automatic buckles.
- Loops for holding the leg straps and the shoulder straps.
- Under-buttock strap.
- Mountain type leg straps optimising comfort and offering great mobility in the harness.
- Chest strap with side adjustment.
- Label holder for storing and recording customer information.
- Sewn-in anti-release stops at the ends of the straps
- Maximum working load (operator and equipment): 150 kg
- Available sizes: S, M, XL, XXL.
- Weight (Size M): 1390 g.
- Polyester webbing.
- Polyester stitching threads.
- Cataphoresis treated steel buckles.
- Option:
 - Work positioning belt.
 - X-PAD.

APPLICABLE STANDARDS

- EN 361/2002

STANDARD PRODUCTS

| Code | Description | Weight (g) |
|--------|-------------|------------|
| 055012 | HT45 S | 1320 |
| 055022 | HT45 M | 1390 |
| 055032 | HT45 XL | 1460 |
| 075532 | HT45 XXL | 1530 |

LOGISTIC INFORMATIONS

| Code | Description | EAN Code | Packaging size (mm) |
|--------|-------------|---------------|---------------------|
| 055012 | HT45 S | 3600230550121 | 140 x 200 x 370 |
| 055022 | HT45 M | 3600230550220 | 140 x 200 x 370 |
| 055032 | HT45 XL | 3600230550329 | 140 x 200 x 370 |
| 075532 | HT45 XXL | 3600230755328 | 140 x 200 x 370 |