

## CERTIFICATE OF CONFORMITY

### N° 17.0153/A-2

#### 1. Applicant

Applicant: Patrick COPIN  
Manufacturer: TRACTEL S.A.S. – RD619 - BP38 Saint-Hilaire-Sous-Romilly - 10102 ROMILLY-SUR-SEINE- France

#### 2. Equipment

Type of equipment: **Anchor device** Type C - EN 795:2012 and CEN/TS 16415:2013  
Trade mark: **TRACTEL**<sup>®</sup>  
Model: **TRAVSMART**  
References: **S2A** – Specificity: Multi-span  
**S2AMP** – Specificity: Single-span

#### 3. Description

Main characteristics :		Components :	Material :	References :
Span:	Multi: 5m min / 15m max Single: 5m min / 30m max	Flexible anchor line:	Ø 8,0mm wire rope in stainless steel 316 - 7x19	057262
User:	5 person (maximum load 100kg) 3 person (maximum load 150kg)	Anchor connector:	Stainless steel 316	039822
Cable tension:	100 daN	Mobile anchor: Slider	Stainless steel 431	251349
Direction of use:	Wall / floor / ceiling	Intermediate anchor – Floor / Wall:	Cupro-aluminium	193847
Angle of use:	max. 15°	Intermediate anchor – Ceiling:	Cupro-aluminium	193857
Energy absorber:	at both ends	Curve intermediate anchor (90°) – Floor / Wall:	Cupro-aluminium	193867
This device has no:	joint, entry/exit line fitting, flexible support fixed on anchor, no metallic material without evidence of durability	Curve intermediate anchor (90°) – Ceiling:	Cupro-aluminium	193877
Compatibility:	This device can be used with retractable fall arresters BLOCFOR B1.8A ESD, B1.8B ESD, B5 ESD, B6 ESD, B10 ESD, B20ESD and Guided type fall arresters including a flexible anchor line (halyard and twisted rope type) STOPFOR B and STOPFOR K	INRS energy absorber: (x2)	Stainless steel	066688
		Tensioner:	Stainless steel 316L	040742
		Tension indicator:	Stainless steel	066858
		Wedge end fitting:	Cupro-aluminium	193837


#### 4. Technical referential

The assessment of conformity was conducted taking into account the provisions of:  
- European standard EN 795:2012 "Personal fall protection equipment - Anchor devices".  
- Technical Specification CEN/TS 16415:2013 "Personal fall protection equipment - Anchor devices - Recommendations for anchor devices for use by more than one person simultaneously" CEN/TS 16415:2013

#### 5. Conclusion

The aforementioned anchor device type C, described in conformity report n° 17.0153, conforms to the requirements of the EN 795:2012 and CEN/TS 16415:2013.

06/01/2020  
The PPE Technical Manager



Validation électronique

*This certificate cancels and replaces the one edited under the same number on 06/12/2019  
This certificate includes one page. No duplicate will be issued.*

*This type of equipment is not a Personal Protective Equipment against falls from height, the present certificate of conformity is not an EU type examination certificate delivered by a notified body.*