

APPLICATION

The work positioning lanyard LCM05 is a manually adjusted tensioner-reducer. This device works on a low-stretch rope diameter of 12.5mm and length of 2 to 4m. The LCM05 is compact and ergonomic and perfectly suited for work positioning



TECHNICAL CHARACTERISTICS

- Tensioner made in aluminum
- Braided rope, diameter 12.5mm
- Steel screw connector M10, 17mm opening
- Aluminium connector M41, 25mm opening
- Strength 15kN
- Option Cut-resistant sheath, PA strap, 50cm

DESCRIPTION

The lanyard LCM05 is equipped with a compact, ergonomic tensioner-reducer. The device is made of high-strength aluminium. The LCM05 is moved along the rope by simply pressing on the tensioner jaw. In the event of a fall or loss of balance, the tensioner automatically locks.

The unit is supplied with a low-stretch rope diameter of 12.5mm and length of 2m, 3m or 4m, equipped with a connector M10 on the tensioner and a connector M41 on the end of the rope.

These are used to support the person who is working, these lanyard are not fall protection devices

NORM

- Conforms to standard EN358.

CODES

| DESIGNATION | CODE | EAN code |
|----------------------|-------|---------------|
| LCM05 M10 /M41 lg 2m | 79122 | 3600230791227 |
| LCM05 M10 /M41 lg 3m | 79132 | 3600230791326 |
| LCM05 M10 /M41 lg 4m | 79142 | 3600230791425 |