

APPLICATION:

The HT45 A harnesses are technical harnesses designed for the construction and industrial markets. Their ergonomics ensure optimal comfort. They are designed for long term work. They are simple to use and easy to adjust.

The HT45 A harness is widely used for work on roofs, ladders or scaffolding.

The HT45 A harness is designed for all operations where the operator needs to use his fall arrester from the front.

The sternal attachment point facilitates the handling of fall arresters on flexible anchor line and ensures better comfort at the workstation.

It is equipped with mountain-type leg loop which optimise comfort and provide great mobility in the harness. The label holder allows the storage and recording of customer information.



TECHNICAL FEATURES:

- 1 Dorsal attachment.
- 1 Sternal attachment.
- Quick adjustment of shoulder straps.
- Locking and adjustment of straps with automatic buckles.
- Mountain-type leg loops.
- Elastomer loops on leg and shoulder straps.
- Thoracic strap with lateral adjustment.
- Buttock strap.
- Label holder.
- End stops against strap release.
- Maximum authorized weight (operator and equipment): 150 kg.
- Available sizes: S, M, XL.
- Weight (Size M): 1570 g.

OPTIONS:

- Work positioning belt
- X PAD

CE CERTIFICATION:

- Notified Body: Alienor certification CE2754
- N°: 2754/0352/160/10/20/0643

STANDARDS COMPLIANCE:

- EN 361

ASSOCIATED EQUIPMENT:

- EN 795 Anchorage system
- EN 362 Connectors
- EN 363 Fall arrest system

CODES:

DESIGNATION	CODE	EAN CODES
HT45 S A	53072	3600230530727
HT45 M A	53082	3600230530826
HT45 XL A	53092	3600230530925