

## APPLICATIONS

The HT55 harness is simple to use and easy to adjust. It is designed for all operations where the operator needs to use the fall arrest from the front (roofer, ladder work).

The sternal attachment point facilitates the handling of rope grabbers and ensures better comfort at the workstation. The large diameter of the back attachment point makes it easier to attach the connector to the operator's back.

Its ergonomic design ensures optimum comfort. It is designed for long duration work.

It is equipped with an X-PAD which increases comfort and distributes the weight of the harness over the operator's shoulders. It also makes it easier to put on the harness.

This technical harness is widely used for interventions on roofs, ladders or scaffolding.

This harness is ideal for construction work.



## TECHNICAL CHARACTERISTICS

- 1 back attachment point, 1 sternal attachment point.
- Quick adjustment of shoulder straps by sliding bar buckle.
- Fastening and adjustment of straps by flat buckles.
- Loops for holding the leg straps and the shoulder straps.
- Under-buttock strap.
- Mountain type leg straps optimising comfort and offering great mobility in the harness.
- Chest strap with side adjustment.
- Label holder for storing and recording customer information.
- Sewn-in anti-release stops at the ends of the straps
- Maximum working load (operator and equipment): 150 kg
- Fall indicator integrated into the straps to check if the harness has stopped a fall.
- Available sizes: S, M, XL.
- Weight (Size M): 1650 g.
- Polyester webbing.
- Polyester stitching threads.
- Cataphoresis treated steel buckles.
- Option: Work positioning belt.

## APPLICABLE STANDARDS

- EN 361/2002

## STANDARD PRODUCTS

Code	Description	Weight (g)
065592	HT55S	1600
065602	HT55M	1650
065612	HT55XL	1720

## LOGISTIC INFORMATIONS

Code	Description	EAN Code	Packaging size (mm)
065592	HT55S	3600230655925	140 x 200 x 370
065602	HT55M	3600230656021	140 x 200 x 370
065612	HT55XL	3600230656120	140 x 200 x 370