

APPLICATIONS

The HT22 harness is simple to use and easy to adjust, it is designed for all operations where the operator needs to use his fall arrester from the front, (roofing, ladder work).

The sternal attachment point facilitates the handling of rope fall arresters and ensures better comfort at the workstation. This harness is ideal for industrial maintenance interventions.



TECHNICAL CHARACTERISTICS

- 1 dorsal attachment point, 1 sternal attachment point.
- Quick adjustment of shoulder straps with sliding buckles.
- Locking and adjustment of straps with flat buckles.
- Elastomer loops on leg and shoulder straps.
- Buttock strap.
- End stop against strap release.
- Maximum authorized weight (user and equipment): 150 kg.
- Available sizes: S, M, XL, XXL.
- Weight (size M): 1050 g.
- Polyester webbing.
- Polyester sewing threads.
- Cataphoresis treated steel buckles.
- Option Work positioning belt.
- Option X-PAD.

APPLICABLES STANDARDS

- EN 361.

EXISTING PRODUCTS

Code	Description	Weight (g)
031592	HT 22 S	1000
014002	HT 22 M	1050
028502	HT 22 XL	1100
079412	HT 22 XXL	1150

LOGISTIC INFORMATION

Code	Description	EAN Code	Weight (g) (incl. packaging)	Packaging size (mm)
031592	HT 22 S	3600230315928	1216	138 x 120 x 222
014002	HT 22 M	3600230140025	1268	138 x 120 x 222
028502	HT 22 XL	3600230285023	1328	138 x 120 x 222
079412	HT 22 XXL	3600230794129	1363	138 x 120 x 222