

## APPLICATIONS

The HT 22 A harness is simple to use and easy to adjust. It is designed for all operations where the operator needs to use the fall arrest from the front (roofer, ladder work).

The sternal attachment point facilitates the handling of rope grabbers and ensures better comfort at the workstation. This harness is ideal for industrial maintenance.

The automatic buckles make it easy to put on and adjust the harness.



## TECHNICAL CHARACTERISTICS

- 1 back attachment point, 1 sternal attachment point.
- Quick adjustment of shoulder straps by sliding bar buckle.
- Fastening and adjustment of straps by automatic buckles.
- Loops for holding the leg straps and the shoulder straps.
- Under-buttock strap.
- Sewn-in anti-release stops at the ends of the straps
- Maximum working load (operator and equipment): 150 kg
- Available sizes: S, M, XL.
- Weight (Size M): 1230g.
- Polyester webbing.
- Polyester stitching threads.
- Cataphoresis treated steel buckles.
- Automatic buckles:
  - Aluminium body.
  - Other parts in cataphoresis treated steel.
- Option:
  - Work positioning belt.
  - X-PAD.

## APPLICABLE STANDARDS

- EN361.

## EXISTING PRODUCTS

| Code   | Description | Weight (g) |
|--------|-------------|------------|
| 031832 | HT 22 S A   | 1180       |
| 031822 | HT 22 M A   | 1230       |
| 031842 | HT 22 XL A  | 1280       |
| 079422 | HT 22 XL A  | 1350       |

## LOGISTIC INFORMATION

| Code   | Description | EAN Code      | Weight (incl. packaging) | Packaging size  |
|--------|-------------|---------------|--------------------------|-----------------|
| 031832 | HT 22 S A   | 3600230318325 |                          | 138 x 120 x 222 |
| 031822 | HT 22 M A   | 3600230318226 |                          | 138 x 120 x 222 |
| 031842 | HT 22 XL A  | 3600230318424 |                          | 138 x 120 x 222 |
| 079422 | HT 22 XL A  | 3600230794228 |                          | 138 x 120 x 222 |