

APPLICATION:

The HT43 harness is simple to use and easy to adjust, it is designed for all operations where the operator needs to use his or her fall arrester from the front. Its 3 front attachment points ensure great versatility. It is possible to connect an EN 358 adjustable lanyard between the two thoracic attachment points for a short intervention, but it is imperative to have a fall arrest system for this use. The sternal attachment point facilitates the handling of fall arresters on flexible anchor line and ensures better comfort at the workplace. This harness is ideal for industrial maintenance work.



TECHNICAL FEATURES:

- 1 Dorsal attachment.
- 1 Sternal attachment.
- 2 Thoracic attachments.
- Quick adjustment of shoulder straps.
- Locking and adjustment of straps with flat buckles.
- Elastomer loops on leg and shoulder straps.
- Buttock strap.
- End stops against strap release.
- Maximum authorized weight (operator and equipment): 150 kg.
- Available sizes: S, M, XL.
- Weight (Size M): 1240 g.

OPTIONS:

- Work positioning belt
- X PAD

CE CERTIFICATION:

- Notified Body: Alienor certification CE2754
- N°: 2754/0352/160/10/20/0636

STANDARDS COMPLIANCE:

- EN 361

ASSOCIATED EQUIPMENT:

- EN 795 Anchorage system
- EN 362 Connectors
- EN 363 Fall arrest system

CODES:

DESIGNATION	CODE	EAN CODES
HT 43 S	33302	3600230333021
HT 43 M	33292	3600230332925
HT 43 XL	33312	3600230333120